


















ANELLI DI SUPPORTO	COD	Materiali	bar	Temperatura (°C)	Velocità (m/sec)
	BUR08	POM PTFE	-	-60 bis 100 -200 bis 260	-
	BUR09	POM PTFE	-	-60 bis 100 -200 bis 260	-
	BUR10	POM PTFE	-	-60 bis 100 -200 bis 260	-
	BUR11	POM PTFE	-	-60 bis 100 -200 bis 260	-
	BUR12	POM PTFE	-	-60 bis 100 -200 bis 260	-
	BUR13	POM PTFE	-	-60 bis 100 -200 bis 260	-



ANELLI DI GUIDA	COD	Materiali	bar	Temperatura (°C)	Velocità (m/sec)
	BWR01	POM PTFE Polyester-fabric*	-	-60 bis 100 -200 bis 260 -40 bis 130	4
	BWR01A	POM PTFE	-	-60 bis 100 -200 bis 260	4
	BWR03	POM PTFE	-	-60 bis 100 -200 bis 260	4
	BWR04	POM PTFE	-	-60 bis 100 -200 bis 260	4
	BWR05	POM PTFE	-	-60 bis 100 -200 bis 260	4
	BWR06	POM PTFE	-	-60 bis 100 -200 bis 260	4
	BWR07	POM PTFE	-	-60 bis 100 -200 bis 260	4
	BWR08	POM PTFE	-	-60 bis 100 -200 bis 260	4
	BWR09	-	-	-	-

\* Varie dimensioni disponibili su ruote.